

JPL TILO

JPL TILO

Precision-formula solution for design-critical finishes and fine-detail work.



PRODUCT BENEFIT

- | | | | | | |
|--|-------------------|--|-----------------|--|----------------|
| | Flexible | | Strong Adhesion | | Exterior Grade |
| | Minimum Thickness | | User Friendly | | Eco Friendly |
| | Single Component | | Water Resistant | | Versatile |

UTILITY AREAS

- Swimming Pools
- Water Tank
- Balcony
- Terrace
- Toilet Floor
- Kitchen Floor
- Rooms (Interiors)
- Toilet Walls
- Dry Walls
- Mivan Walls
- Pre-Cast Walls
- Kitchen Walls

PACKAGE AVAILABLE

Available in Transparent and Pigmented Format

Shelf Life - 12 Months

Color - Clear/ Pigmented



1 Ltr. Can

4 Ltr. Can

20 Ltr. Can

APPLICATION PROCEDURE

1. The surface should be dry, clean and stable.
2. Please ensure the surface is levelled and a proper slope is given wherever necessary.
3. The surface can be levelled with JPL Terrashield Fine.
4. Apply JPL Tilo on the back side of the tile to a thickness of 1 to 2 mm and press it from all sides and the centre.
5. The oozed-out material can be used in the next tile.
6. Ensure that the corners are filled.
7. Allow it to dry for 24 hours.
8. Physically ready for the moment after 96 hours.

